STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Surface.Zoom

STD-000578-0036

Configured Product

Light Source

SL98

Light Source Size

6mm LES

CCT

2700K

Beam

Zoom 13.7° to 48.1°

Finish

Matt Black

Dimming

Driver specific

Attachments

None

Cable route

Flying Lead

Secondary Lensing Accessories

With accessories

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Surface.Zoom

STD-000578-0036



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments
Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description
ZTA.50.Surface Zoom is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, Wall Wash, Zoom and Framing projector options.

Key Features
• Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Zoomable beam to allow easy and quick beam adjustment without the need for additional optics.
• Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
• High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
• Customisable accessories: can house up to one lens accessory and various attachments.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.

ZTA.50.Surface.Zoom

STD-000578-0036

Compliance

ZTA.50.Surface.Zoom

STD-000578-0036

Technical

Supply	Remote constant current LED driver required
Light source	6mm LES COB
Initial output	**SL90** 8W 32Vf at 250mA 2700K • 1087lm • 136lm/W 3000K • 1133lm • 141lm/W 3500K • 1144lm • 143lm/W 4000K • 1175lm • 147lm/W **SL98** 8.6W 34.4Vf at 250mA 2400K • 733lm • 85lm/W 2700K • 863lm • 100lm/W 3000K • 923lm • 107lm/W 3500K • 923lm • 107lm/W 4000K • 974lm • 113lm/W
Light distribution	Zoom 13.7° - 48.1°
Lumen maintenance	L90 B0 in excess of 94,000 hours
Colour consistency	2 SDCM
IP rating	IP20
Weight	0.43kg

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Surface.Zoom

STD-000578-0036

Service Commitment