

## ZTA.70.LV Track.Wall Wash

STD-000583-0018

### Configured Product

Light Source

SL90

CCT

2700K

Finish

Matt Black

Track adaptor colour


White

Dimming

0-10V

Secondary Lensing Accessories

Without accessories



Modular high-performance, low voltage track-mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.


## Product Description

ZTA.70.LV Track Wall Wash is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Compatible with 48V Stucchi Multisystem EVO track, this spotlight includes integral dimming control gear.

The spotlight can accommodate up to two lens accessories and multiple attachments, making it highly customisable for various lighting needs.

## Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Fixed optics can be easily swapped to decorative frosted diffuser options.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Capable of ceiling, wall and table mounting.



Compliance



## Technical

**Supply** 48V supply to Stucchi Multisystem EVO track

**Light source** 14mm LES COB

**Initial output** **SL90** 17.2W 34.3Vf at  
500mA

2700K · 2613lm · 152lm/W  
3000K · 2736lm · 159lm/W  
3500K · 2768lm · 161lm/W  
4000K · 2751lm · 160lm/W

**SL98** 18.1W 33Vf at 550mA

2700K · 2129lm · 118lm/W  
3000K · 2274lm · 126lm/W  
3500K · 2337lm · 129lm/W  
4000K · 2388lm · 132lm/W

**Light distribution** Wall Wash 78.1° x 33.2°

**Lumen maintenance** L90 B0 in excess of 94,000 hours

**Colour consistency** 2 SDCM

**IP rating** IP20

**Weight** 0.75kg

## Service Commitment

