

ZTA.70.Surface

STD-000590-0165

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

3000K

Beam

Narrow 11°

Finish

Custom Painted

Dimming

N/A

Attachments

None

Cable route

Through Base

Cable Length

Custom

Secondary Lensing Accessories

With accessories



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.70.Surface is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. The spotlight can accommodate up to two lens accessories and multiple attachments, making it highly customisable for various lighting needs.

Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-performance lighting: Up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: Can house up to two lens accessories and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



Compliance



Technical

Supply

Remote constant current LED driver required

Light source

6mm LES COB

9mm LES COB

14mm LES COB

Initial output

SL90 8W 32Vf at 250mA

2700K · 1087lm · 136lm/W
 3000K · 1133lm · 141lm/W
 3500K · 1144lm · 143lm/W
 4000K · 1175lm · 147lm/W

SL98 8.6W 34.4Vf at 250mA

2700K · 863lm · 100lm/W
 3000K · 923lm · 107lm/W
 3500K · 923lm · 107lm/W
 4000K · 974lm · 113lm/W

SL90 11.8W 33.8Vf at 350mA

2700K · 1822lm · 154lm/W
 3000K · 1908lm · 161lm/W
 3500K · 1929lm · 163lm/W
 4000K · 1919lm · 162lm/W

SL98 10.6W 30.4Vf at 350mA

2700K · 1205lm · 113lm/W
 3000K · 1288lm · 121lm/W
 3500K · 1313lm · 124lm/W
 4000K · 1352lm · 127lm/W

SL90 20.9W 34.8Vf at 600mA

2700K · 3097lm · 148lm/W
 3000K · 3243lm · 155lm/W
 3500K · 3280lm · 157lm/W
 4000K · 3261lm · 156lm/W

SL98 23.5W 33.5Vf at 700mA

2700K · 2669lm · 114lm/W
 3000K · 2852lm · 122lm/W
 3500K · 2909lm · 124lm/W
 4000K · 2973lm · 127lm/W

Light distribution

Very Narrow 7.3°

Very Narrow 2 9.6°

Narrow 11°

Medium 26.7°

Flood 36.8°

Wide Flood 55.4°

Extra Wide Flood 85.4°

Very Narrow 11.1°

Narrow 14.4°

Narrow 2 15.1°

Medium 25.1°

Flood 35.1°

Wide Flood 54.1°

Extra Wide Flood 82.9°

Narrow 16.9°

Narrow 2 21.4°

Medium 22°

Medium 2 24.7°

Flood 32.4°

Wide Flood 51.6°

Extra Wide Flood 79.6°

| | |
|--------------------|----------------------------------|
| Lumen maintenance | L90 B0 in excess of 94,000 hours |
| Colour consistency | 2 SDCM |
| IP rating | IP20 |
| Weight | 0.84kg |

Service Commitment

