

ZTA.70.Surface.Wall Wash

STD-000591-0019

Configured Product

Light Source

SL90

CCT

2700K

Supply

Constant Current

Finish

Matt Black

Dimming

Driver specific

Attachments

Barn Doors (specified separately)

Cable route


Through Base

Cable Length

500mm

Secondary Lensing Accessories

With accessories



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments.

Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.70.Surface.Wall Wash is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. The spotlight can accommodate up to two lens accessories and multiple attachments, making it highly customisable for various lighting needs.

Key Features

- Sustainable Construction: Made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Versatile Adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-Performance Lighting: Up to 98 CRI LEDs.
- Customisable Accessories: Can house up to two lens accessories and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



Compliance



Technical

Supply Remote constant current LED driver required

Light source 14mm LES COB

Initial output **SL90** 17.2W 34.3Vf at
500mA

2700K · 2613lm · 152lm/W
3000K · 2736lm · 159lm/W
3500K · 2768lm · 161lm/W
4000K · 2751lm · 160lm/W

SL98 18.1W 33Vf at 550mA

2700K · 2129lm · 118lm/W
3000K · 2274lm · 126lm/W
3500K · 2337lm · 129lm/W
4000K · 2388lm · 132lm/W

Light distribution Wall Wash 78.1° x 33.2°

Lumen maintenance L90 B0 in excess of 94,000 hours

Colour consistency 2 SDCM

IP rating IP20

Weight 0.84kg

Service Commitment

