

ZTA.50.LV Track.Framer

STD-000593-0048

Configured Product

Light Source

SL98

Light Source Size

9mm LES

CCT

3000K

Finish

RAL 9003 Signal White

Framer type

Adjustable Beam

Track adaptor colour

White

Dimming



Casambi Wireless

Gobo Holder

No

Softening Diffuser/Accessory

Yes



Modular high-performance, low voltage track-mounted spotlight system, for interior architectural applications such as Museums, Galleries and Retail. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

## Product Description

ZTA.50.LV Track is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between Framing projector, fixed optic, Wall Wash and Zoom options.

Fixed uses a Wide Flood spread for long throws. Adjustable uses a Zoom lens to allow the user to narrow in on very fine details. Both are capable of holding a gobo.

## Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish.
- Framing attachment can be easily swapped to fixed optics, Zoom and Wall Wash.
- The easy-to-adjust fins allow for precision positioning to sharply define light on pieces of artwork.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Ceiling mounting only: designed exclusively for ceiling installations



Compliance



# Technical

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply             | 48V supply to Stucchi Multisystem EVO track                                                                                                                                                                                                                                                                                                                                                                      |
| Light source       | 9mm LES COB                                                                                                                                                                                                                                                                                                                                                                                                      |
| Initial output     | <div><div>SL90 11.8W 33.8Vf at 350mA</div><div>2700K · 1822lm · 154lm/W</div><div>3000K · 1908lm · 161lm/W</div><div>3500K · 1929lm · 163lm/W</div><div>4000K · 1919lm · 162lm/W</div><div>SL98 10.6W 30.4Vf at 350mA</div><div>2400K · 1085lm · 102lm/W</div><div>2700K · 1205lm · 113lm/W</div><div>3000K · 1288lm · 121lm/W</div><div>3500K · 1313lm · 124lm/W</div><div>4000K · 1352lm · 127lm/W</div></div> |
| Light distribution | <div>Adjustable 10° to 28.9°</div> <div>Fixed 49.3°</div>                                                                                                                                                                                                                                                                                                                                                        |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours                                                                                                                                                                                                                                                                                                                                                                                 |
| Colour consistency | 2 SDCM                                                                                                                                                                                                                                                                                                                                                                                                           |
| IP rating          | IP20                                                                                                                                                                                                                                                                                                                                                                                                             |
| Weight             | 1kg                                                                                                                                                                                                                                                                                                                                                                                                              |

---

Service Commitment

